

GRUNDFOS A WIDE RANGE OF QUALITY PUMPS
50 Hz



BE > THINK > INNOVATE >

GRUNDFOS 



A global business

With over 14 000 employees and annual production of some 10 million pump units a year, Grundfos is one of the world's leading pump manufacturers. More than 73 companies right across all the continents of the globe help to bring pumps to every corner of the world, from supplying drinking water to Antarctic expeditions, irrigation of Dutch tulips, groundwater monitoring beneath waste heaps in Germany, to air-conditioning in Egyptian hotels.

Efficient, sustainable products

Grundfos is constantly striving to make its products more userfriendly and reliable – and also energy-saving and efficient, so that both users and the environment benefit from their improvements.

Grundfos pumps are equipped with ultramodern electronics, allowing them to regulate their output according to current needs. This not only ensures convenience for the user, but also saves a great deal of energy.

Research and development

In order to maintain its leading position, Grundfos constantly places a great deal of emphasis on customer-oriented research and development; customers are consulted when new products are developed or when



established products are improved.


Research and development make use of the latest technology within the pump industry, collaborating with universities and higher education institutions in search of new and better solutions for the design and function of the products.

Corporate values

The Grundfos Group is based on values such as sustainability, openness, trustworthiness, responsibility, and also on partnership with clients, suppliers and the whole of society around us, with a focus on humanity that concerns our own employees as well as the many millions who benefit from water that is procured, utilised and removed as wastewater with the help of Grundfos pumps.


Pumps for all purposes

No matter for which purpose an efficient and energy saving pump solution is required, Grundfos offers a high-quality solution.



Heating and hot water service systems

Circulator pumps for circulation of hot water in central and district heating systems and circulation in domestic hot water service systems.



Cooling and air-conditioning systems

Circulator pumps for circulation of cold water and other liquids in cooling and air-conditioning systems.



Industrial applications

A wide range of pumps for the transfer of water, cooling lubricants and other liquids in industrial and process systems.



Pressure boosting and liquid transfer

Vertical and horizontal, centrifugal pumps and pressure boosting systems for liquid transfer and boosting of hot and cold water.



Groundwater supply

Submersible and dry installed pumps for groundwater supply, irrigation and groundwater lowering.



Domestic water supply

Submersible pumps, jet pumps, multistage centrifugal pumps and compact systems for water supply in homes, gardens and hobby applications.




Wastewater

Drainage, effluent and sewage pumps, for a wide range of applications in building services, the industry as well as transfer of raw sewage in municipal sewage systems and treatment plants.



Environmental applications

Purpose-built submersible pumps for remedial pumping of contaminated groundwater and for sampling for water quality analyses.



Dosing

Dosing pumps, disinfection systems and measuring & control for wastewater treatment systems, swimming pools and industry.



Renewable-energy systems

Renewable-energy-based water supply systems suitable for remote locations not connected to the electricity supply grid.

Product and application overview

Heating and hot water service systems

Control MPC	10
Control MPC Series 2000	11
GRUNDFOS ALPHA2, GRUNDFOS ALPHA+, UPS, UP Series 100	8
GRUNDFOS COMFORT UP-N, UP(S)-B Series 100	8
GRUNDFOS MAGNA, Series 2000	9
TPE Series 1000	10
NB, NBG	11
NBE, NBGE	12
NK, NKG	11
NKE, NKGE	12
TP	9
TPE Series 2000	9
UPS Series 200	8

Cooling and air-conditioning systems

CHI, CHIU	18
CHIE	18
CH, CHN	27
CHV	28
CR, CRI, CRN	18
CRE, CRIE, CRNE	20
CV, CPV, CPH	20
Control MPC	10
Control MPC Series 2000	11
GRUNDFOS ALPHA2, GRUNDFOS ALPHA+, UPS, UP Series 100	8
GRUNDFOS COMFORT UP-N, UP(S)-B Series 100	8
TPE Series 1000	10
NB, NBG	11
NBE, NBGE	12
NK, NKG	11
NKE, NKGE	12
TP	9
TPE Series 2000	9
UPS Series 200	8

Industrial applications

AMD, AMG, AFG	30
BMP	23
BM, BMB	23
BME, BMET	24
BMEX	24
CH, CHN	27
CHI, CHIU	18
CHIE	18
CHV	28
Contra	21
Control MPC	10
Control MPC Series 2000	11
CR, CRI, CRN	18
CRE, CRIE, CRNE	20
CRT	19
CV, CPV, CPH	20
DP, EF, SE1 and SEV	33
DME	14
DDI	14
DMS	14
DMI	15
DMX	15
DMH	15
durietta	21
DW	30
Euro-HYGIA®	20
F&B-HYGIA®	21
Hydro MPC/Hydro 1000, Hydro Solo-E/-S, Hydro Multi-E/-S	23
TPE Series 1000	10
MAXA and MAXANA	22
MTB	13
NB, NBG	11
NBE, NBGE	12
NK, NKG	11
NKE, NKGE	12
NOVAlobe	22
S pumps	32
SRP pumps	32
SEN	33
SE	33
SIPLA	22
SPK, MTH, CRK, MTR, MTA	13
SPKE, MTRE	13
Pressure tanks	29

Product and application overview

Pressure boosting and liquid transfer

BM, BMB	23
BME, BMET	24
BMEX	24
CH, CHN	27
CHI, CHIU	18
CHIE	18
CHV booster	29
CHV	28
Control MPC	10
Control MPC Series 2000	11
CR, CRI, CRN	18
CR, CRN high pressure	19
CRE, CRIE, CRNE	20
CRT	19
CV, CPV, CPH	20
GP	17
HS	12
Hydro MPC/Hydro 1000, Hydro Solo-E/-S, Hydro Multi-E/-S	23
TPE Series 1000	10
MQ	28
NB, NBG	11
NBE, NBGE	12
NK, NKG	11
NKE, NKGE	12

Groundwater supply

SP A, SP, SP-G	25
SQ, SQE	24
Pressure tanks	29

Domestic water supply

CH, CHN	27
CHV booster	29
CHV	28
CR, CRI, CRN	18
CRE, CRIE, CRNE	20
Hydro MPC/Hydro 1000, Hydro Solo-E/-S, Hydro Multi-E/-S	23
JP	27
MQ	28
RMQ	28
SP A, SP, SP-G	25
SQ, SQE	24
Pressure tanks	29

Wastewater

AMD, AMG, AFG	30
CHI, CHIU	18
CHIE	18
DP, EF, SE1 and SEV	33
Modular Controls solutions	34
DME	14
DDI	14
DMS	14
DMI	15
DMX	15
DMH	15
DW	30
Unilift CC, KP, AP12, AP35/50, AP35B/50B	29
Lifting stations	31
Sololift+	31
Liftaway B and C	31
Conlift	32
S pumps	32
SRP pumps	32
SEG	30
SEN	33
SE	33

Environmental applications

CR, CRI, CRN	18
CRE, CRIE, CRNE	20
CRT	19
MP 1	26
SQE-NE, SP-NE	26

Dosing

DME	14
DDI	14
DMS	14
DMI	15
DMX	15
DMH	15
Dosing pump accessories	16
Conex DIA, Conex DIS	16
DIP	16
Conex DIA-G, Conex DIS-G	17
DIT	17

Renewable-energy systems


SQFlex	26
--------	----





GRUNDFOS ALPHA2, GRUNDFOS ALPHA+, UPS, UP Series 100

Circulator pumps, canned-rotor type



Technical data

Flow, Q:	max. 10 m ³ /h
Head, H:	max. 12 m
Liquid temp.:	-25 °C to +110 °C
Operat. pressure:	max. 10 bar

Applications

- Circulation of hot or cold water in
- Heating systems
 - Domestic hot water systems
 - Cooling and air-conditioning systems.

Features and benefits

- Low-energy
Energy labelling class C to A
- Maintenance-free
- Low-noise
- Wide range.


Options

- Automatic performance adjustment
- Display of actual power consumption
- Automatic Night SetBack
- Simple installation - external plug for electrical connection
- Single-speed or 2- or 3-speed performance adjustment
- Twin-head versions.



GRUNDFOS COMFORT UP-N, UP(S)-B Series 100

Circulator pumps, canned-rotor type



Technical data

Flow, Q:	max. 10.5 m ³ /h
Head, H:	max. 7 m
Liquid temp.:	-25 °C to +110 °C
Operat. pressure:	max. 10 bar

Applications

- Circulation of hot or cold water in
- Domestic hot water recirculation
 - Heating systems
 - Domestic hot water systems
 - Cooling and air-conditioning systems.

Features and benefits

- Maintenance-free
- Low-noise
- Low-energy
- Wide range
- Corrosion-resistant stainless steel/brass pump housing.


Options

- 24-hour timer
- Adjustable thermostat.



UPS Series 200

Circulator pumps, canned-rotor type



Technical data

Flow, Q:	max. 70 m ³ /h
Head, H:	max. 18 m
Liquid temp.:	-10 °C to +120 °C
Operat. pressure:	max. 10 bar

Applications

- Circulation of hot or cold water in
- Heating systems
 - Domestic hot water systems
 - Cooling and air-conditioning systems.

Features and benefits

- Maintenance-free
- Built-in thermal switch
- Low-noise
- Low-energy
Energy labelling up to class B
- Single-phase with built-in protection module
- Wide range.


Options

- Protection module
- Relay module with fault signal or operating output
- Bronze pump housing
- Twin-head versions



GRUNDFOS MAGNA, Series 2000

Circulator pumps, canned-rotor type - electronically controlled



Technical data

Flow, Q: max. 90 m³/h
 Head, H: max. 12 m
 Liquid temp.: +15 °C to +110 °C
 Operat. pressure: max. 10 bar

Applications

Circulation of hot water in

- Heating systems in blocks of flats, schools, hospitals, hotels, industry etc.

Features and benefits

- Low-noise
- Low-energy
Energy labelling: Class A
- Wide range
- Automatic performance adjustment
- Simple installation - no extra equipment or fittings required
- Safe selection.


Options

- Stainless steel pump housing
- Twin-head versions
- Wireless remote control, R100
- Communication via GENIbus or LON.



TP

Circulator pumps, close-coupled type



Technical data

Flow, Q: max. 4600 m³/h
 Head, H: max. 170 m
 Liquid temp.: -25 °C to +150 °C
 Operat. pressure: max. 25 bar

Applications

Circulation of hot or cold water in

- Heating systems
- District heating plants
- Local heating plants
- Domestic hot water systems
- Cooling and air-conditioning systems.

Features and benefits

- Compact design
- Wide range
- Standard motor
- Service-friendly
- Various types of shaft seals depending on liquid, temperature and pressure.


Options

- Bronze pump housing
- Twin-head versions.



TPE Series 2000

Single-stage, centrifugal pumps - electronically controlled



Technical data

Flow, Q: max. 370 m³/h
 Head, H: max. 90 m
 Liquid temp.: -25 °C to +140 °C
 Operat. pressure: max. 16 bar

Applications

Circulation of hot or cold water in

- Heating systems
- Domestic hot water systems
- Cooling and air-conditioning systems.

Features and benefits

- Low-energy
- Adaptation to existing operating conditions
- Simple installation


Options

- Parallel operation
- Wireless remote control, R100
- Communication via GENIbus or LON
- Twin-head versions.



TPE Series 1000

Single-stage, centrifugal pumps - electronically controlled



Technical data

Flow, Q: max. 370 m³/h
 Head, H: max. 90 m
 Liquid temp.: -25 °C to +140 °C
 Operat. pressure: max. 16 bar

Applications

The pumps are suitable for liquid transfer in

- District heating plants
- Cooling and air-conditioning systems
- Industrial plants.

Features and benefits

- Low-energy
- Adaptation to existing operating conditions
- Simple installation
- Many control facilities
- Wireless remote control, R100
- Communication via GENIbus or LON.



R100

Wireless remote control

Applications

All pumps designed for wireless communication.

Features and benefits

- Simple and quick installation of the pump
- Reading out of various operating and fault signals
- Printing out of status information.



Control MPC

Pump controllers

Technical data

- Control of up to 6 pumps in parallel
- Motors from 0.37-75 kW can be connected (on request up to 315 kW)
- Enclosure class: IP 54

Applications

- Heating systems
- Air-conditioning systems
- Cooling systems
- Pressure booster systems
- Industrial processes
- Water supply systems.

Designed for

- CR(E), CRI(E) and CRN(E)
- NB(E), NBG(E)
- NK(E), NKG(E)
- TP
- TPE Series 1000
- TPE Series 2000
- HS
- SP
- MAGNA, UPE Series 2000.

Features and benefits

- Easy installation and start-up
- Simple control
- Application-optimised software
- Modular solution with possibility of expansion
- Data communication via Ethernet, LON, Profibus etc.



Control MPC Series 2000

Pump controllers

Technical data

- Control of up to 6 Grundfos MAGNA, UPE, TPE Series 2000 pumps of identical pump type and size
- Mains supply: 1x100-240 V
- All motor sizes can be connected
- Enclosure class: IP 54

Applications

- Heating systems
- Air-conditioning systems.

Features

Optimal adaptation of the performance to the demand by closed-loop control of

- proportional differential pressure
- constant differential pressure


By means of an external sensor, Control MPC Series 2000 ensures optimal adaptation of the performance to the demand by closed-loop control of

- differential pressure (remote)
- flow rate
- temperature
- temperature difference.



NB, NBG

Single-stage standard pumps



Technical data

Flow, Q:	max. 1000 m ³ /h
Head, H:	max. 160 m
Liquid temp.:	-25 °C to +140 °C
Operat. pressure:	max. 16 bar

Applications

The pumps are suitable for liquid transfer in

- District heating plants
- Heating systems for blocks of flats
- Air-conditioning systems
- Cooling systems
- Washdown systems
- Other industrial systems.

Features and benefits

- Standard dimensions according to EN and ISO standards
- Compact design
- Flexible pump range
- Standard motor
- Adaptable to any application and performance
- EN 12 756 shaft seal.


Optional

- Various types of shaft seal depending on liquid, temperature and pressure
- Cast iron, bronze or stainless steel impeller
- Cast iron or stainless steel pump housing.



NK, NKG

Single-stage standard pumps according to EN733, ISO2858 and ISO5199



Technical data

Flow, Q:	max. 2000 m ³ /h
Head, H:	max. 160 m
Liquid temp.:	-25 °C to +140 °C
Operat. pressure:	max. 16 bar

Applications

The pumps are suitable for liquid transfer in

- District heating plants
- Water supply systems
- Air-conditioning systems
- Cooling system
- Washdown system
- Fire fighting systems
- Other industrial systems.

Features and benefits

- Standard dimensions according to EN or ISO standards
- Robust design
- Wide range
- Standard motor
- Adaptable to any application and performance
- En 12 756 shaft seal.


Optional

- Various types of shaft seal depending on liquid, temperature and pressure
- Cast iron, bronze or stainless steel impeller
- Cast iron or stainless steel pump housing.



NBE, NBGE

Single-stage standard pumps - electronically controlled



Technical data

Flow, Q: max. 550 m³/h
 Head, H: max. 100 m
 Liquid temp.: -25 °C to +140 °C
 Operat. pressure: max. 16 bar

Applications

The pumps are suitable for liquid transfer in

- District heating plants
- Heating systems for blocks of flats
- Air-conditioning systems
- Cooling systems
- Washdown systems
- Other industrial systems.

Features and benefits

- Standard dimensions according to EN and ISO standards
- Compact design
- Flexible pump range
- Standard motor
- Adaptable to any application and performance
- EN 12 756 shaft seal.


Optional

- Various types of shaft seal depending on liquid, temperature and pressure
- Cast iron, bronze or stainless steel impeller
- Cast iron or stainless steel pump housing.



NKE, NKGE

Single-stage standard pumps according to EN733, ISO2858 and ISO5199 - electronically controlled



Technical data

Flow, Q: max. 550 m³/h
 Head, H: max. 100 m
 Liquid temp.: -25 °C to + 140 °C
 Operat. pressure: max. 16 bar

Applications

The pumps are suitable for liquid transfer in


- District heating plants
- Water supply systems
- Air-conditioning systems
- Cooling systems
- Washdown systems
- Other industrial systems.

Features and benefits

- Standard dimensions according to EN and ISO standards
- Robust design
- Wide range
- Standard motor
- Adaptable to any application and performance
- EN 12 756 shaft seal.


Options

- Various types of shaft seal depending on liquid, temperature and pressure
- Cast iron, bronze or stainless steel impeller
- Cast iron or stainless steel pump housing.



HS

Horizontal split case pumps.



Technical data

Flow, Q: max. 2500 m³/h
 Head, H: max. 148 m
 Liquid temp.: 0 °C to + 90 °C
 Operat. pressure: max. 16 bar

Applications

The pumps are suitable for liquid transfer in

- District heating plants
- Water supply systems
- Air-conditioning systems
- Cooling systems
- Irrigation systems
- Other industrial systems.

Features and benefits

- Flange dimensions according to EN 1092-2 (DIN 2501) standard
- Robust design
- Wide range
- Standard motor
- Adaptable to any application and performance
- Shaft seal according to EN 12756


Options

- Ductile iron and cast iron pump casing
- Stuffing box
- Bronze, aluminium bronze and stainless steel impeller



SPK, MTH, CRK, MTR, MTA

Multistage centrifugal immersible pumps



Technical data

Flow, Q: max. 85 m³/h
 Head, H: max. 238 m
 Liquid temp.: -20 °C to + 90 °C
 Operat. pressure: max. 25 bar

Applications

The pumps are suitable for liquid transfer in

- Spark machine tools
- Grinding machines
- Machining centres
- Cooling units
- Industrial washing machines
- Filtering systems
- Lathes
- Swarf conveyors
- Temperature control
- Boiler feed.


Features and benefits

- Flexible installation length
- Wide range
- Reliability
- Service-friendly
- Simple installation
- Space-saving
- High efficiency.



SPKE, MTR

Multistage centrifugal immersible pumps - electronically controlled



Technical data

Flow, Q: max. 22 m³/h
 Head, H: max. 245 m
 Liquid temp.: -10 °C to + 90 °C
 Operat. pressure: max. 25 bar

Applications

The pumps are suitable for

- Boiler feeding systems
- Pumping of cooling lubricants
- Water treatment systems
- Temperature control
- Industrial washing machines.

Features and benefits

- Wide range
- Reliability
- Wireless remote control, R100
- High-efficiency
- Space saving
- Service friendly
- Many control facilities.


Options

- Wireless remote control, R100.



MTB

Single-stage inline pump with semi-open impeller



Technical data

Flow, Q: max. 90 m³/h
 Head, H: max. 47 m
 Liquid temp.: -10 °C to + 90 °C
 Operat. pressure: max. 16 bar

Applications

The MTB is specially designed for machine tool and washing/cleaning applications such as:

- Machine centres
- Coolant systems
- Filtration plants
- Grinding machines
- Part cleaning systems
- Other industrial applications, where semi-open impellers are needed.


Features and benefits

- Standard dimension according to EN and ISO standards
- Compact design
- Semi-open impeller / effective solid handling
- Standard EFF1 motor.



DME

Compact diaphragm dosing pumps



Technical data

Capacity, Q: max. 940 l/h
 Pressure, p: max. 18 bar
 Liquid temp.: max. +50 °C

Applications

- water treatment
- wastewater treatment
- washing systems
- swimming pools
- process plants
- filtration systems
- reverse osmosis.


Features and benefits

- Capacity setting in ml/h or l/h
- Full diaphragm control
- Stroke-speed or stroke-frequency capacity control
- Control panel with display and one-touch buttons
- Front- or side-fitted control panel
- Manual/pulse control
- Control panel lock
- 4-20 mA control
- Pulse-/timer-based batch control
- Anti-cavitation function
- Easy calibration function
- Fieldbus communication module (option)
- Diaphragm leakage sensor.



DDI

Digital diaphragm dosing pumps



Technical data

Capacity, Q: max. 150 l/h
 Pressure, p: max. 16 bar
 Liquid temp.: max. +50 °C

Applications

- water treatment
- wastewater treatment
- washing systems
- swimming pools
- process plants
- paper production
- food and beverage industry.


Features and benefits

- Powerful stepper motor (DDI 209) or brushless DC motor (DDI 222)
- Capacity setting in ml/h or l/h
- Smooth dosing through variable speed
- Reliable dosing of viscous liquids
- Front- or top-fitted control panel (DDI 222: side-fitted)
- Manual/pulse control
- 4-20 mA control
- Easy calibration and dosing of small liquid quantities or degassing media (DDI 209 with Plus³)
- Pioneering system for flow and pressure monitoring in the dosing head (control variant AF).
- PROFIBUS interface (control variant AP).



DMS

Compact diaphragm dosing pumps



Technical data

Capacity, Q: max. 12 l/h
 Pressure, p: max. 11 bar
 Liquid temp.: max. +50 °C

Applications

- water treatment
- wastewater treatment
- washing systems
- swimming pools
- process plants.


Features and benefits

- Capacity setting in ml/h or l/h
- Full diaphragm control
- Stroke-frequency capacity control
- Control panel with display and one-touch buttons
- Front- or side-fitted control panel
- Manual control
- Pulse control (control variants A and AR)
- 4-20 mA control (control variants A and AR)
- Alarm relay output (control variant AR)
- Control panel lock
- Easy calibration function.



DMI

Robust diaphragm dosing pumps



Technical data

Capacity, Q: max. 18 l/h
 Pressure, p: max. 16 bar
 Liquid temp.: max. +50 °C

Applications

- water treatment
- wastewater treatment
- washing systems
- swimming pools
- process plants.


Features and benefits

- Well-proven synchronous motor technology
- Silent operation (45 dB(A))
- Flexible installation: built-in pump for OEM solutions
- Front- or top-fitted control panel
- Manual/pulse control
- Contact signal control with multiplier/divisor (control variant AR)
- Stroke-frequency control (control variant AR)
- Easy calibration and dosing of small liquid quantities or degassing media (dosing heads with Plus³ system)
- DMI is also available in a special version with injection unit and water meter (Unidos).



DMX

Motor-driven diaphragm dosing pumps



Technical data

Capacity, Q: max. 4000 l/h
 (Pump with two heads:
 2 x 4000 l/h)
 Pressure, p: max. 16 bar
 Liquid temp.: max. +50 °C

Applications

- Drinking-water treatment
- Wastewater treatment (settlement/sludge treatment)
- Pulp/paper and textile industries.

Features and benefits

- Robust design
- Stroke-length adjustment.


Options

- Pulse control (control variant AR)
- Analog control (control variant AR)
- Level input from storage tank (control variant AR)
- Motor frequency control
- ATEX (DMX 226).



DMH

Oscillating positive displacement pumps with hydraulic diaphragm control



Technical data

Capacity, Q: max. 1500 l/h
 (Pump with two heads:
 2 x 1500 l/h)
 Pressure, p: max. 200 bar
 Liquid temp.: max. +90 °C

Applications

- Oil refinery industry
- Heavy-duty applications
- Drinking-water treatment
- Wastewater treatment (settlement/sludge treatment)
- Pulp/paper and textile industries.

Features and benefits

- Designed for heavy-duty operation
- Stroke-length adjustment.

Options

- Servomotor for stroke-length adjustment
- Motor frequency control
- Available with API 675 approval
- Available with ATEX approval.



Dosing pump accessories

Accessories for dosing pumps and dosing systems

Dosing pump accessories

- installation kits
- tubing
- pump connections
- foot valves
- suction lines
- injection valves
- pressure-relief valves
- pressure-loading valves
- multi-function valve
- pulsation dampers
- tanks
- agitators and mixers
- automatic venting valves
- diaphragm leakage sensor
- dosing monitor
- flowmeter
- water meter
- cables and plugs.



Conex DIA, Conex DIS

Measurement and control systems for dosing instrumentation

Technical data

Amplifier parameters:

Conex DIA-1: Cl₂, ClO₂, O₃, PAA or H₂O₂, fluoride, pH or redox

Conex DIA-2: 1: Cl₂, ClO₂, O₃ or H₂O₂,
2: pH

Conex DIA-2Q: 1: Cl₂, ClO₂, O₃, PAA or H₂O₂

Conex DIS-C: conductivity (inductive or conductive probes)

Conex DIS-PR: pH or redox

Conex DIS-D: Cl₂, ClO₂ or O₃.

Applications

Instrumentation in disinfection processes:

- drinking water
- industrial water
- wastewater.

Features and benefits

- User-friendly plain-text menu and operator prompting.
- Device calibration feature with plausibility check prevents errors occurring.
- Multilingual menu.
- Self-monitoring feature ensures excellent water quality at all times.
- All disturbance variables are compensated which means that chemical consumption is reduced to very low levels.
- Available as a preassembled system (amplifier and measuring cell) mounted on a plate and ready for connection.



DIP

Measurement and control systems for dosing instrumentation

Technical data

Amplifier parameters:

DIP: 1: Cl₂, ClO₂ or O₃

2: pH,

3: redox.

Applications

Instrumentation in disinfection processes:

- swimming-pool water

Features and benefits

- User-friendly plain-text menu and operator prompting.
- Device calibration feature with plausibility check prevents errors occurring.
- Multilingual menu.
- Self-monitoring feature ensures excellent water quality at all times.
- All disturbance variables are compensated which means that chemical consumption is reduced to very low levels.
- Available as a preassembled system (amplifier and measuring cell) mounted on a plate and ready for connection.



Conex DIA-G, Conex DIS-G

Gas warning systems

Technical data

- Conex DIS-G: gas warning system for Cl_2 , ClO_2 , O_3 (amperometric probes)
- Conex DIA-G: gas warning system for Cl_2 , ClO_2 , O_3 (amperometric and potentiostatic probes) and NH_3 , HCl (potentiostatic probes).

Applications

- gas dosing installations
- gas storage rooms.

Features and benefits

- Optimum safety
- Very short response time
- Automatic sensor recognition
- Bus communication with CAN bus interfaces (internal and external)
- Simultaneous measurement and display of two measuring parameters.



DIT

Photometer

Technical data

Measuring parameters:

- aluminium
- ammonium
- chloride
- chlorine (free and total)
- chlorine dioxide
- chromium
- cyanide
- cyanuric acid
- iron
- fluoride
- hydrazine
- manganese
- nickel
- nitrate
- nitrite
- ozone
- phosphate
- pH
- redox potential (ORP)
- temperature.

Applications

The compact hand photometer DIT is dedicated for routine analysis in water treatment monitoring. It provides photometric and/or electrochemical measuring system.


Features and benefits

- Up to 20 parameters can be measured
- Precise and well-reproducible measuring values
- Long-term stable even after several measurements
- Multi-lingual plain-text operator prompting
- Patented, two-beam principle with carrier frequency technology compensates for the effects of turbidity or external light.



GP

Swimming-pool pumps



Technical data

- Flow, Q: max. 26 m³/h
- Head, H: max. 17.5 m
- Liquid temp.: 0 °C to +40 °C
- Operat. pres.: max. 3 bar

Applications

The pumps are suitable for circulation of swimming-pool water in small and medium sized swimming pools.

Features and benefits

- Built-in motor protection
- Stainless-steel shaft
- Low sound level
- Self-priming down to 2 m
- Corrosion-resistant materials
- No need for special service tools
- Quick and easy to repair.


Options

- Integrated heating unit
- Level sensor
- Control panels.



CHI, CHIU

Multistage centrifugal pumps



Technical data

Flow, Q:	max. 29 m ³ /h
Head, H:	max. 58 m
Liquid temp.:	
CHI2 to CHI12:	-20 °C to +110 °C
CHI15 and CHI20:	-20 °C to +70 °C
Operat. pres.:	max. 10 bar

Applications

The pumps are suitable for liquid transfer in

- Water treatment systems
- Industrial washing and dishwashing machines
- Pressure boosting of process water
- Heating and cooling in industrial processes
- Air-conditioning systems
- Airwashing, moisturization, humidification (softened water)
- Water supply and pressure boosting (potable water, also slightly chlorinated).


Features and benefits

- Compact design
- Wide range
- Suitable for slightly aggressive liquids
- Low noise
- Leakage-free (CHIU only).



CHIE

Multistage centrifugal pumps - electronically controlled



Technical data

Flow, Q:	max. 14 m ³ /h
Head, H:	max. 58 m
Liquid temp.:	-20 °C to +110 °C
Operat. pres.:	max. 10 bar

Applications

The pumps are suitable for liquid transfer in

- Cooling systems
- Industrial washing systems
- Aquafarms
- Fertilizer systems
- Dosing systems
- Industrial plants.

Features and benefits

- Compact design
- Wide range
- Suitable for slightly aggressive liquids
- Many control facilities.


Options

- Wireless remote control, R100.



CR, CRI, CRN

Multistage centrifugal pumps



Technical data

Flow, Q:	max. 180 m ³ /h
Head, H:	max. 330 m
Liquid temp.:	-40 °C to +180 °C
Operat. pres.:	max. 33 bar

Applications

The pumps are suitable for liquid transfer in

- Washing systems
- Cooling and air-conditioning systems
- Water supply systems
- Water treatment systems
- Fire fighting systems
- Industrial plants
- Boiler feeding systems.

Features and benefits

- Reliability
- High efficiency
- Service-friendly
- Space-saving
- Suitable for slightly aggressive liquids.


Options

- Dry-running protection and motor protection via LiqTec.



CR, CRN high pressure

Multistage centrifugal pumps



Technical data

Flow, Q:	max. 180 m ³ /h
Head, H:	max. 480 m
Liquid temp.:	-30 °C to +120 °C
Operat. pres.:	max. 50 bar

Applications

The pumps are suitable for liquid transfer in

- Washing systems
- Water treatment systems
- Industrial plants
- Boiler feeding systems.

Features and benefits

- Reliability
- High pressures
- Service-friendly
- Space-saving
- Suitable for slightly aggressive liquids
- Single pump solution enabling high pressure.


Options

- Dry-running protection and motor protection via LiqTec.



CRT

Multistage centrifugal pumps



Technical data

Flow, Q:	max. 22 m ³ /h
Head, H:	max. 250 m
Liquid temp.:	-20 °C to +120 °C
Operat. pres.:	max. 25 bar

Applications

The pumps are suitable for liquid transfer in

- Process water systems
- Washing in cleaning systems
- Sea water systems
- Pumping of acids and alkalis
- Ultra filtration systems
- Reverse osmosis systems
- Swimming baths.

Features and benefits

- High corrosion resistance
- Reliability
- High efficiency
- Service-friendly
- Space-saving.

Options

- Dry-running protection and motor protection via LiqTec.



LiqTec

Control and monitoring unit

Applications

- Monitoring and protection of pumps and processes.


Features and benefits

- Protection against dry running
- Protection against liquid temperatures exceeding 130 °C ±5 °C
- Protection against too high motor temperatures
- Manual or automatic restarting possible from a remote PC
- Simple installation - plug and play technology
- Robust sensor.



CV, CPV, CPH

Multistage centrifugal pumps



Technical data

Flow, Q:	max. 560 m ³ /h
Head, H:	max. 200 m
Liquid temp.:	-15 °C to +120 °C
Operat. pres.:	max. 20 bar

Applications

The pumps are suitable for liquid transfer in

- Washing systems
- Cooling and air-conditioning systems
- Water supply systems
- Water treatment systems
- Fire fighting systems
- Industrial plants
- Boiler feeding systems.


Features and benefits

- Low-speed (4-pole motors)
- Heavy-duty
- Low-noise
- Vertical and horizontal installation.



CRE, CRIE, CRNE

Multistage centrifugal pumps - electronically controlled



Technical data

Flow, Q:	max. 120 m ³ /h
Head, H:	max. 250 m
Liquid temp.:	-40 °C to +180 °C
Operat. pressure:	max. 33 bar

Applications

The pumps are suitable for liquid transfer in

- Washing systems
- Cooling and air-conditioning systems
- Water supply systems
- Water treatment systems
- Fire fighting systems
- Industrial plants
- Boiler feeding systems.

Features and benefits

- Wide range
- Reliability
- In-line design
- High efficiency
- Service-friendly
- Space-saving
- Many control facilities.


Options

- Wireless remote control, R100.



Euro-HYGIA®

Single-stage, end-suction sanitary pumps



Technical data

Flow, Q:	max. 108 m ³ /h
Head, H:	max. 70 m
Operat. temp.:	+95 °C (+150 °C on request)
Operat. pressure:	max. 16 bar

Applications

- Liquid transfer in breweries and dairies
- Pure water systems (WFI)
- Process pumping in pharmaceutical/cosmetic industry
- CIP (Cleaning-In-Place) systems
- Bio fuel application.

Features and benefits

- Unique hygienic design (QHD, EHEDG and 3A standards)
- CIP and SIP capable (DIN EN 12462)
- Customised solutions
- Materials: AISI 316L (DIN EN 1.4404/1.4435)
- Gentle liquid handling.


Options

- Electronically speed controlled versions
- ATEX-certified pumps
- Wide range of impeller designs
- Three surface standards.



F&B-HYGIA®

Single-stage, end-suction sanitary pumps



Technical data

Flow, Q: max. 105 m³/h
 Head, H: max. 70 m
 Operat. temp.: +95 °C
 (+150 °C on request)
 Operat. pressure: max. 16 bar

Applications

- Liquid transfer in breweries and dairies
- Soft-drink mixing
- Syrup and sugar solutions
- Frying oil and blood processing
- Fruit-drink and yeast pumping
- Food processing.

Features and benefits

- Unique hygienic design.
- CIP and SIP capable (DIN EN 12462)
- Materials: AISI 316 (DIN EN 1.4404)
- Compact design.


Options

- Large selection of supports for motor and pump
- Several mechanical shaft seal types
- Wide range of pipe connections
- With or without motor shroud.



Contra

Single- and multi-stage, end-suction sanitary pumps



Technical data

Flow, Q: max. 55 m³/h
 Head, H: max. 160 m
 Operat. temp.: +95 °C
 (+150 °C on request)
 Operat. pressure: max. 25 bar

Applications

- Liquid transfer in breweries and dairies
- Carbonising systems
- Food processing plants
- Purification systems
- Pure water systems (WFI)
- Surface treatment systems
- CIP feeding systems
- Bio fuel application.

Features and benefits

- Unique hygienic design (QHD, EHEDG and 3A standards)
- CIP and SIP capable (DIN EN 12462)
- High efficiency
- Materials: AISI 316L (DIN EN 1.4404/1.4435).


Options

- Electronically speed-controlled versions
- ATEX-certified pumps
- Fully drainable versions.



durietta

Single- or multistage, end-suction sanitary pumps



Technical data

Flow, Q: max. 6 m³/h
 Head, H: max. 70 m
 Operat. temp.: +90 °C
 Operat. pressure: max. 8 bar

Applications

- Pumping of liquids in micro breweries and dairies
- Bottling systems
- Purification systems
- Drinking water systems
- Industrial applications.

Features and benefits

- Unique hygienic design to 3A standards.
- CIP capable (DIN EN 12462)
- Materials: AISI 316 (DIN EN 1.4404/1.4571)
- Compact design.


Options

- Electronically speed-controlled versions
- Wide range of pipe connections
- Vertical version
- Various shaft seals.



SIPLA

Single-stage, self-priming side-channel sanitary pumps



Technical data

Flow, Q: max. 90 m³/h
 Head, H: max. 56 m
 Operat. temp.: +95 °C
 (+140 °C on request)
 Operat. pressure: max. 10 bar

Applications

- CIP return pumping
- Transfer of glycerine
- Transfer of yeast
- Transfer of whey.

Features and benefits

- Meets the 3A sanitary standard
- High air-content handling
- Efficient priming
- Robust, service friendly.


Options

- Electronically speed controlled versions
- ATEX-certified pumps
- Various shaft seals
- Various connections.



MAXA and MAXANA

End-suction process pumps



Technical data

Flow, Q: up to max. 820 m³/h
 Head, H: up to max. 97 m
 Operat. temp.: +95 °C
 (+150 °C on request)
 Operat. pressure: max. 10 bar

Applications

- Gentle pumping of mash and wort for beer filtration (hot side)
- Liquid transfer in dairies
- Water treatment plants
- Chemical and environmental handling systems
- Liquids with high content of solid particles
- Bio fuel application.

Features and benefits

- Optimised hydraulics
- Gentle product handling
- Materials: AISI 316 (DIN EN 1.4404)
- Service and repair friendly.


Options

- Electronically speed controlled versions
- ATEX-certified pumps
- Electro-polished versions
- Double mechanical shaft seals (tandem/back-to-back).



NOVALobe

Rotary lobe pump with positive displacement



Technical data

Displacement: 0.03 to 1.29 l/rev.
 Max. diff. pressure: 16 bar
 Viscosity: max. 1,000,00 cP
 Operat. temp.: +150 °C
 (+300 °C on request)
 Operat. pressure: up to 40 bar

Applications

- Pumping of high-viscosity products, e.g. yoghurt, mayonnaise and shampoo
- Pumping of products requiring gentle handling, e.g. cheese curd, yeast and vaccine/fermentation broth
- Filling and bottling applications.

Features and benefits

- Unique hygienic design (QHD and 3A)
- Robust construction
- Service-friendly
- CIP and SIP capable (DIN EN 12462)
- Materials: AISI 316 (DIN EN 1.4404/1.4435).


Options

- Integrated pressure-relief valve
- Wide range of shaft seals (elastomer)
- Thermal jackets
- Aseptic front cover.



Hydro MPC/Hydro 1000, Hydro Solo-E/-S, Hydro Multi-E/-S

Complete pressure boosting systems



Technical data

Flow, Q: max. 720 m³/h
Head, H: max. 160 m
Liquid temp.: 0 °C to +70 °C
Operat. pressure: max. 16 bar

Applications

Hydro booster systems are suitable for pressure boosting in

- Water supply systems
- Irrigation systems
- Water treatment systems
- Fire fighting systems
- Industrial plants.

Features and benefits

- Easy installation and start-up
- Userfriendly setting and monitoring
- Application-optimised software
- Modular solution with possibility of expansion
- Data communication via Ethernet, LON, Profibus etc.
- Reliability
- High efficiency



BMP

Piston pumps designed for transport of fluids under high pressure.

Technical data

Flow, Q: max. 10.2 m³/h
Head, H: max. 1630 m
Liquid temp.: 3 °C to +50 °C
Operat. pressure: max. 160 bar

Applications

BMP pumps are suitable for a variety of applications ranging from pumping of potable water to pumping of chemicals.

- Cleaning/washing
- Injecting
- Misting
- Processing
- Desalination of brackish water and seawater.


Features and benefits

- High efficiency
- Small and light pump
- Generates insignificant pulsations in the discharge line
- No preventive maintenance required
- Long service life
- Few wear parts
- Wide speed control range
- Extreme recirculation capability without overheating (up to 90%)
- Lubricated by the pumped liquid.



BM, BMB

4", 6", 8" booster modules



Technical data

Flow, Q: max. 260 m³/h
Head, H: max. 430 m
Liquid temp.: 0 °C to +40 °C
Operat. pressure: max. 80 bar


Applications

The booster modules are suitable for pressure boosting in

- Reverse osmosis systems
- Water supply systems
- Water treatment systems
- Industrial plants.


Features and benefits

- Various material versions
- Low-noise
- Simple installation
- Modular design
- Compact design
- Leakage-free.



BME, BMET

High-pressure booster systems



Technical data

Flow, Q: max. 95 m³/h
 Head, H: max. 700 m
 Liquid temp.: 0 °C to +40 °C
 Operat. pressure: max. 70 bar

Applications

The booster systems are suitable for pressure boosting in

- Reverse osmosis systems
- Water supply systems
- Water treatment systems
- Industrial plants.


Features and benefits

- High-pressure/high-flow
- Low-energy
- Simple installation
- Compact design.



BMEX

Grundfos booster system BMEX for energy recovery in Sea Water Reverse Osmosis (SWRO) systems.



Technical data

Permeate per day: 500 to 2500 m³
 Head, H: max. 810 m
 Ambient temp.: +40 °C
 Operat. pressure: max. 80 bar

Applications

- Desalination of brackish water and seawater.


Features and benefits

- Energy recovery up to 60%, compared to conventional systems, resulting in short payback period
- Corrosion- and wear-resistant internal ceramic components
- Couplings for easy installation
- High-grade stainless steel used on frame and manifold
- Large flows and high heads
- Motor and bearings are standard components
- Maintenance-free shaft seal
- V-belt drive with high efficiency
- Easy to dismantle for service.



SQ, SQE

3" submersible pumps



Technical data

Flow, Q: max. 9 m³/h
 Head, H: max. 210 m
 Liquid temp.: 0 °C to +40 °C
 Installation depth: max. 150 m

Applications

The pumps are suitable for

- Domestic water supply systems
- Groundwater supply to waterworks
- Irrigation in horticulture and agriculture
- Groundwater lowering
- Industrial applications.

Features and benefits

- Integrated dry-running protection
- Soft start
- Over- and undervoltage protection
- High efficiency.


Options

- SQE can be protected, monitored and controlled by CU 300 and CU 301 via R100.



SP A, SP, SP-G

4", 6", 8", 10", 12" submersible pumps



Technical data

Flow, Q: max. 470 m³/h
 Head, H: max. 670 m
 Liquid temp.: 0 °C to +60 °C
 Installation depth: max. 600 m

Applications

- The pumps are suitable for
- Groundwater supply to waterworks
 - Irrigation in horticulture and agriculture
 - Groundwater lowering
 - Pressure boosting
 - Industrial applications.

Features and benefits

- High efficiency
- Long service life as all components are stainless steel
- Motor protection via MP 204.

Options

- Data can be monitored and controlled via MP 204/R100.



MS motors

Stainless steel 4" and 6" submersible motors

Motor sizes

4" motor: 0.37 to 7.5 kW
 6" motor: 5.5 to 30 kW

Applications

The Grundfos MS submersible motors can be fitted on all Grundfos SP A, SP pumps and can be used in the high-pressure booster modules, type BM and BMB.

Features and benefits

- Overtemperature protection by means of a built-in Tempcon temperature transmitter
- Standardized NEMA head and shaft end
- Completely encapsulated in stainless steel
- Liquid cooled and has liquid lubricated bearings.

Options

- Material variants available.



MMS motors

Stainless steel 6", 8", 10", 12" rewindable submersible motors

Motor sizes

6" motor: 3.7 to 37 kW
 8" motor: 22 to 110 kW
 10" motor: 75 to 190 kW
 12" motor: 147 to 250 kW

Applications

The Grundfos MMS submersible motors can be fitted on all Grundfos SP and SP-G pumps.

Features and benefits

- Wide range of rewindable motors
- Easily rewinded
- Protection against upthrust
- High efficiency
- 6" and 8" have standardized NEMA head and shaft end
- Mechanical shaft seal, ceramic/carbon or SiC/SiC
- PVC or PE/PA windings.


Options

- Material variants available
- Overtemperature protection via Pt100.



SQE-NE, SP-NE

Environmental pumps



Technical data

Flow, Q:	max. 22 m ³ /h
Head, H:	max. 215 m
Liquid temp.:	0 °C to +40 °C
Instal. depth:	max. 600 m

Applications

- The pumps are suitable for
- Pumping up contaminated groundwater
 - Sampling
 - Remedial pumping.

Features and benefits


SQE-NE

- Same features and benefits as SQE, SP-NE
- Same features and benefits as SP.



MP 1

Environmental pumps



Technical data


Flow, Q:	max. 2.4 m ³ /h
Head, H:	max. 95 m
Liquid temp.:	0 °C to +35 °C

Applications

- The pumps are suitable for
- Sampling.


Features and benefits

- Compact design
- Fit into 50 mm boreholes.



SQFlex

Renewable-energy based water supply systems



Technical data

Flow, Q:	max. 90 m ³ /day
Head, H:	max. 200 m
Liquid temp.:	0 °C to +40 °C
Voltage supply:	30-300 VDC or 1 x 90-240 V, 50/60 Hz
Instal. depth:	max. 150 m

Applications

The SQFlex systems are suitable for remote locations, such as:

- Villages, schools, hospitals, single-family houses
- Farms and irrigation of greenhouses
- Game parks and game farms
- Conservation areas.

Features and benefits

- Energy supply: Solar modules, wind turbine, generator or batteries
- Simple installation
- Reliable water supply
- Virtually no maintenance
- Expansion possibilities
- Cost-efficient pumping
- Dry-running protection.



MP 204, CU 300, CU 301

Control and monitoring units

Applications

Monitoring and protection of pump installations

Features and benefits

- Protection against dry running and too high motor temperature
- Constant monitoring of pump energy consumption
- Reading out of operating data via R100.


Options

- Connection to large control systems via bus-communication
- Connection of sensors enabling control based on sensor signals.



JP

Self-priming jet pumps



Technical data

Flow, Q: max. 5 m³/h
 Head, H: max. 48 m
 Liquid temp.: 0 °C to +55 °C
 Operat. pressure: max. 6 bar

Applications

The pumps are suitable for liquid transfer in

- Households
- Gardens
- Hobby activities
- Agriculture
- Horticulture
- Small industries.

Features and benefits

- Self-priming
- Stable operation even in case of air pockets in the liquid.


Options

- Automatic start/stop when equipped with Presscontrol
- Booster sets for small-scale water supply.



CH, CHN

Multistage centrifugal pumps



Technical data

Flow, Q: max. 14 m³/h
 Head, H: max. 55 m
 Liquid temp.: 0 °C to +90 °C
 Operat. pressure: max. 10 bar

Applications

The pumps are suitable for liquid transfer in

- Pressure boosting systems
- Domestic water supply systems
- Cooling systems
- Air-conditioning systems
- Horticultural irrigation systems
- Small industrial water supply systems.

Features and benefits

- Compact design
- Robust design
- Full stainless steel design (CHN only)
- Low-noise.


Options

- Booster sets for domestic water supply
- Automatic start/stop when equipped with Presscontrol.



MQ

Multistage centrifugal self-priming pumps



Technical data

Flow, Q:	max. 5 m ³ /h
Head, H:	max. 48 m
Liquid temp.:	0 °C to +35 °C
Operat. pressure:	max. 7.5 bar

Applications

The pumps are suitable for liquid transfer in

- Single- or two-family houses
- Weekend cottages
- Farms
- Greenhouses.


Features and benefits

- All-in-one pressure booster unit
- Easy to install
- Easy to operate
- Self-priming
- Dry-running protection with automatic reset
- Low-noise
- Maintenance-free.



RMQ

Rainwater unit for monitoring and control of rainwater systems



Technical data

Flow, Q:	max. 5 m ³ /h
Head, H:	max. 48 m
Liquid temp.:	0 °C to +35 °C
Operat. pressure:	max. 7.5 bar

Applications

The rainwater unit is suitable for the transfer of water from water collection and utilization systems in:

- Single- or two-family houses
- Weekend cottages
- Farms
- Gardens and greenhouses.

Features and benefits

- Automatic changeover between rainwater tank and integrated main water tank
- Manual changeover between rainwater tank and integrated main water tank
- Acoustic/visual alarm in case of overflow in integrated main water tank.


Options

- Control of additional booster pump
- Backflow sensor in case of overflow in sewers.



CHV

Multistage centrifugal pumps



Technical data

Flow, Q:	max. 8 m ³ /h
Head, H:	max. 93 m
Liquid temp.:	0 °C to +90 °C
Operat. pressure:	max. 12 bar

Applications

The pumps are suitable for liquid transfer in

- Pressure boosting systems
- Domestic water supply systems
- Cooling systems
- Air-conditioning systems
- Horticultural irrigation systems
- Small industrial water supply systems.


Features and benefits

- Compact design
- Robust design
- Low-noise
- Space-saving.



CHV booster

Vertical pressure boosting systems



Technical data

Flow, Q: max. 16 m³/h
 Head, H: max. 93 m
 Liquid temp.: 0 °C to +40 °C
 Operat. pressure: max. 10 bar

Applications

The booster systems are suitable for pressure boosting in

- Small waterworks
- Small blocks of flats
- Hotels
- Stores
- Light industry
- Hospitals
- Schools
- Large houses.

Features and benefits

- One- or two-pump system
- User-friendly controllers
- Reliability
- High efficiency
- Service-friendly.

Options

- Overpressure protection
- Dry-running protection.



Pressure tanks

Diaphragm and bladder tanks

Technical data

Tank size: 8-3000 l
 Liquid temp.: max. +90 °C
 Operat. pressure: max. 16 bar

Applications

The diaphragm and bladder tanks are used in

- Water supply systems in housing
- Pressure boosting systems in housing
- Agriculture
- Horticulture
- Industrial systems.


Features and benefits

- Optimal water supply
- Reduced number of pump starts
- Ideal for drinking water.



Unilift CC, KP, AP12, AP35/50, AP35B/50B

Submersible drainage and effluent pumps



Technical data

Flow, Q: max. 35 m³/h
 Head, H: max. 18 m
 Liquid temp.: 0 °C to +55 °C
 Particle size: ø10-50 mm

Applications

The pumps are suitable for

- drainage of flooded cellars
- pumping of household wastewater
- groundwater lowering
- emptying of swimming pools and excavations
- drainage of drain wells
- emptying of tanks and reservoirs.

Features and benefits

- Simple installation
- Service- and maintenance-free.


Options

- Unilift CC is suitable for low suction
- Unilift AP35/50 and AP35B/50B has vortex impeller
- Unilift AP35B and AP50B has auto-coupling and horizontal outlet.



SEG

Grinder pumps



Technical data

Flow, Q: max. 5 l/s
 Head, H: max. 47 m
 Liquid temp.: 0 °C to +40 °C

Applications

The pumps are suitable for the pumping of wastewater with toilet waste through pipes of 40 mm in diameter and upwards.

Features and benefits

- Service-friendly
- Installation on foot or auto-coupling
- Continuous operation with fully submerged pump
- Built-in motor protection
- SmartTrim
- Improved grinder system
- Totally sealed cable plug.

Options

- Wide range of accessories
- Monitoring and control of one or several pumps.



AMD, AMG, AFG

Mixers and flowmakers

Technical data

Liquid temp.: +5 °C to +40 °C
 pH value: 4 to 10
 Axial thrust: 160 to 3931 N
 Max. dynamic viscosity: 500 mPa s
 Max. density: 1060 kg/m³
 Max. installation depth: 20 m

Applications

The mixers and flowmakers are designed for mixing, i.e. homogenization and suspension, of liquids in

- Municipal wastewater treatment systems
- Industrial processes
- Sludge treatment systems
- Agriculture
- Biogas plant

The mixers and flowmakers are equipped with propellers made of stainless steel or composite material with a diameter between 180 mm and 2300 mm and a rotation speed between 22 min⁻¹ and 1400 min⁻¹.


Features and benefits

- Wide range of flexible installation accessories
- Easy to maintain and service without use of special tools
- Electronic leak sensor in gearbox/shaft seal housing
- Shaft seal protected against abrasive materials
- Self-cleaning stainless steel or polyamide propellers.



DW

Contractor pumps



Technical data

Flow, Q: max. 300 m³/h
 Head, H: max. 100 m
 Liquid temp.: 0 °C to +40 °C

Applications

The pumps are suitable for liquid transfer in

- Tunnels
- Mines
- Quarries
- Gravel pits
- Fish ponds
- Building sites.


Features and benefits

- Extremely hard-wearing due to specially selected materials
- Simple installation
- Service-friendly.



Lifting stations

Complete pumping stations



Technical data

Flow, Q: max. 60 l/s (216 m³/h),
recom. 31 l/s (110 m³/h)
Head, H: max. 29 m
Liquid temp.: 0 °C to +40 °C
Discharge diameter: DN 80 to DN 100

Applications

- The lifting stations are suitable for use in
- Single- and multi-family houses
 - Weekend cottages and summer houses
 - Restaurants
 - Small hotels
 - Sewage systems in the open country
 - Percolation systems.

Features and benefits

- Ready for installation
- Flexible pipe connection
- Cable plug connection
- Unique clamp assembly system
- Single-channel and vortex impellers
- Solids passage up to 100 mm
- Low risk of clogging
- Minimum downtime
- Low operating costs
- Liquidless motor cooling
- Unique cartridge shaft seal
- Modular design.



Sololift+

Domestic lifting stations

Applications

- Sololift+ can be used for:
- extra bathrooms
 - basement installations
 - low-cost bathrooms in holiday cottages
 - added facilities in hotels and guest-houses
 - bathrooms for the elderly or the disabled
 - renovation of offices and other commercial buildings.

Features and benefits

- Unique design with smooth line and rounded edges - fits every modern bathroom environment
- Plug-and-go product - all you need in one package
- Low noise level
- Discharge pipe connection in the side ensures easy maintenance
- Flexible discharge pipe adapters for outer pipe diameters of $\varnothing 23$, $\varnothing 25$, $\varnothing 28$ and $\varnothing 32$ mm
- Thermal overload switch
- Cover without screws - easy service
- Easy connection of extra sanitary appliances.

CWC-3

- Especially designed for wall-hung toilets
- Compact and slim for easy integration into the wall.

C-3

- Especially designed for high liquid temperature wastewater from washing machine or dishwasher
- Compact and slim for easy installation under a wash basin or in a closet.



Liftaway B and C

Domestic lifting stations

Technical data for Liftaway B

Inlet dimension: 3 x DN 100
Discharge connection: DN 40
Effective volume: 40 l

Technical data for Liftaway C

Inlet dimension: 3 x DN 100
+ 1 x DN 40/50
Discharge connection: DN 40
Effective volume: 13 l

Applications

- Liftaway B and C can be used:
- as draining well for the collection of drainage and surface water
 - for the collection and pumping of wastewater from basement and laundry rooms below sewer level
 - for the collection and pumping of wastewater from wash basins, washing machines, showers and floor drains to sewer level
 - for the collection and pumping of rain water.

Features and benefits

- To be fitted with pumps from the Unilift KP and AP range.

Liftaway B

- Telescopic part for easy height adjustment
- Flexible and easy installation.

Liftaway C

- Functional design and easy to clean
- Overflow protection device
- Active carbon filter to eliminate odours
- Compact and slim for easy installation under a wash basin or in a closet.



Conlift

Pump for condensate water

Technical data

Flow:	max. 630 l/h
Head H:	max. 5.3 m
Liquid temp.:	max. 35 °C short periods 80 °C
pH:	min 2.7
Container volume:	2.6 l
Effective volume:	0.85 l

Applications

The Conlift is designed for safe removal of condensate from:

- boilers up to 200 kW
- air-conditioning systems
- cooling and refrigeration systems
- air dehumidifiers
- evaporators.


Features and benefits

- Built-in on/off control via two pressure switch ensures high security
- Built-in alarm and potentialfree contact
- Angular mounting brackets to counteract buoyancy
- LGA approval
- Modern design
- Easy to clean.



S pumps

Supervortex pumps, single- or multi-channel impeller pumps



Technical data

Flow, Q:	max. 2500 l/s
Head, H:	max. 116 m
Liquid temp.:	0 °C to +40 °C
Discharge diameter:	DN 80 to DN 800
Particle size:	max. ø145 mm

Applications

The pumps are suitable for the following applications

- Transfer of wastewater
- Transfer of raw water
- Pumping of sludge-containing water
- Pumping of industrial effluent.

Features and benefits

- Wide range
- SmartTrim
- Operation with/without cooling jacket
- Submerged or dry installation
- Different types of impellers
- Built-in motor protection.


Options

- Control and protection systems
- External cooling water
- External seal flush system
- Sensors for monitoring of pump conditions.



SRP pumps

Submersible re-circulation pumps



Technical data

Flow, Q:	max. 1430 l/s (5130 m ³ /h)
Head, H:	max. 2.1 m
Liquid temp.:	5 °C to +40 °C
Discharge pipe diameter:	DN 300, DN 500 and DN 800

Applications

The pumps are suitable for the following applications

- Re-circulation of sludge within sewage treatment plants
- Storm water pumping.

Features and benefits

- High efficiency stainless steel impeller
- Totally submerged installations
- Built-in motor protection.


Options

- Control and protection systems.



SEN

Submersible stainless steel pumps



Technical data

Flow, Q: max. 215 l/s
(774 m³/h)
Head, H: max. 50 m
Liquid temp.: 0 °C to +40 °C
Discharge diameter: DN 80 to DN 250

Applications

The pumps are suitable for the following applications

- Transfer of wastewater and raw water
- Pumping of highly aggressive liquids
- Pulp and paper industries.

Features and benefits

- SmartTrim
- Operation with/without cooling jacket
- Submerged or dry installation
- Different types of impellers
- Built-in motor protection
- Various executions in stainless steel
- Liquids with a pH value between 2 and 14.


Options

- Control and protection systems
- External cooling water
- External seal flush system
- Sensors for monitoring of pump conditions.



SE

Heavy duty submersible pumps



Technical data

Flow, Q: max. 88 l/s
(315 m³/h)
Head, H: max. 45 m
Liquid temp.: 0 °C to +40 °C
Discharge diameter: DN 65 to DN 150

Applications

The pumps are suitable for the following applications

- Wastewater
- Process water
- Unscreened raw sewage.

Features and benefits

- Cable plug connection
- Unique clamp assembly system
- Single-channel and vortex impellers
- Solids passage up to 100 mm
- Minimum downtime
- Low operating costs
- Liquidless motor cooling
- Unique cartridge shaft seal.


Options

- Control and protection systems
- Motor operation control
- Sensors for monitoring pump conditions.



DP, EF, SE1 and SEV

Drainage, effluent and sewage pumps



Technical data

Flow, Q: max. 19.5 l/s
(70 m³/h)
Head, H: max. 25 m
Liquid temp.: 0 °C to +40 °C
Discharge diameter: Rp 2 to DN 65

Applications

The pumps are suitable for:

- Drainage
- Effluent
- Wastewater
- Process water
- Domestic sewage.

Features and benefits

- Cable plug connection
- Unique clamp connection
- Single-channel and vortex impellers
- Solids passage up to 65 mm
- Unique cartridge shaft seal
- Modular design
- Minimum downtime.

Options

- Control and protection systems
- Motor operation control.



Modular Controls solutions

Applications

The Grundfos Modular Controls system is a control system designed for wastewater and water supply installations where advanced control and data communication are required.

- Wastewater main pumping stations
- Mining
- Dewatering.

Features and benefits

- Actual water level and flow measurement
- Monitoring of pumped volume, pump efficiency, specific energy, etc.
- Accurate overflow monitoring and measurement
- Power consumption
- Pump sensors for monitoring of temperature, moisture, water in oil, etc.
- Load monitoring and power factor
- Phase sequence and phase missing
- Current and voltage unbalance.

Argentina

Bombas GRUNDFOS de Argentina S.A.
Ruta Panamericana km. 37.500 Lote 34A
1619 - Garin
Pcia. de Buenos Aires
Phone: +54-3327 414 444
Telefax: +54-3327 411 111

Australia

GRUNDFOS Pumps Pty. Ltd.
P.O. Box 2040
Regency Park
South Australia 5942
Phone: +61-8-8461-4611
Telefax: +61-8-8340 0155

Austria

GRUNDFOS Pumpen Vertrieb Ges.m.b.H.
Grundfosstraße 2
A-5082 Grödig/Salzburg
Tel.: +43-6246-883-0
Telefax: +43-6246-883-30

Belgium

N.V. GRUNDFOS Bellux S.A.
Boomssesteenweg 81-83
B-2630 Aartselaar
Tél.: +32-3-870 7300
Télécopie: +32-3-870 7301

Belorussia

Представительство ГРУНДФОС в Минске
220090 Минск ул.Олешева 14
Телефон: (8632) 62-40-49
Факс: (8632) 62-40-49

Bosnia/Herzegovina

GRUNDFOS Sarajevo
Paromlinska br. 16,
BiH-71000 Sarajevo
Phone: +387 33 713290
Telefax: +387 33 231795

Brazil

Mark GRUNDFOS Ltda.
Av. Humberto de Alencar Castelo Branco, 630
CEP 09850 - 300
São Bernardo do Campo - SP
Phone: +55-11 4393 5533
Telefax: +55-11 4343 5015

Bulgaria

GRUNDFOS Pumpen Vertrieb
Representative Office - Bulgaria
Bulgaria, 1421 Sofia
Lozenetz District
105-107 Arsenalski blvd.
Phone: +359 2963 3820, 2963 5653
Telefax: +359 2963 1305

Canada

GRUNDFOS Canada Inc.
2941 Brighton Road
Oakville, Ontario
L6H 6C9
Phone: +1-905 829 9533
Telefax: +1-905 829 9512

China

GRUNDFOS Pumps (Shanghai) Co. Ltd.
51 Floor, Raffles City
No. 268 Xi Zang Road. (M)
Shanghai 200001
PRC
Phone: +86-021-612 252 22
Telefax: +86-021-612 253 33

Croatia

GRUNDFOS predstavništvo Zagreb
Čebini 37, Buzin
HR-10000 Zagreb
Phone: +385 1 6595 400
Telefax: +385 1 6595 499

Czech Republic

GRUNDFOS s.r.o.
Čajkovského 21
779 00 Olomouc
Phone: +420-585-716 111
Telefax: +420-585-716 299

Denmark

GRUNDFOS DK A/S
Martin Bachs Vej 3
DK-8850 Bjerringbro
Tlf.: +45-87 50 50 50
Telefax: +45-87 50 51 51
E-mail: info_GDK@grundfos.com
www.grundfos.com/DK

Estonia

GRUNDFOS Pumps Eesti OÜ
Peterburi tee 92G
11415 Tallinn
Tel: + 372 606 1690
Fax: + 372 606 1691

Finland

OY GRUNDFOS Pumput AB
Mestarintie 11
FIN-01730 Vantaa
Phone: +358-3066 5650
Telefax: +358-3066 5650

France

Pompes GRUNDFOS Distribution S.A.
Parc d'Activités de Chesnes
57, rue de Malacombe
F-38290 St. Quentin Fallavier (Lyon)
Tél.: +33-4 74 82 15 15
Télécopie: +33-4 74 94 10 51

Germany

GRUNDFOS GMBH
Schlüterstr. 33
40699 Erkrath
Tel.: +49-(0) 211 929 69-0
Telefax: +49-(0) 211 929 69-3799
e-mail: info@grundfos.de
Service in Deutschland:
e-mail: kundendienst@grundfos.de

Greece

GRUNDFOS Hellas A.E.B.E.
20th km. Athinon-Markopoulou Av.
P.O. Box 71
GR-19002 Peania
Phone: +0030-210-66 83 400
Telefax: +0030-210-66 46 273

Hong Kong

GRUNDFOS Pumps (Hong Kong) Ltd.
Unit 1, Ground floor
Siu Wai Industrial Centre
29-33 Wing Hong Street &
68 King Lam Street, Cheung Sha Wan
Kowloon
Phone: +852-27861706 / 27861741
Telefax: +852-27858664

Hungary

GRUNDFOS Hungária Kft.
Park u. 8
H-2045 Törökbálint,
Phone: +36-23 511 110
Telefax: +36-23 511 111

India

GRUNDFOS Pumps India Private Limited
118 Old Mahabalipuram Road
Thoraipakkam
Chennai 600 096
Phone: +91-44 2496 6800

Indonesia

PT GRUNDFOS Pompa
Jl. Rawa Sumur III, Blok III / CC-1
Kawasan Industri, Pulogadung
Jakarta 13930
Phone: +62-21-460 6909
Telefax: +62-21-460 6910 / 460 6901

Ireland

GRUNDFOS (Ireland) Ltd.
Unit A, Merrywell Business Park
Ballymount Road Lower
Dublin 12
Phone: +353-1-4089 800
Telefax: +353-1-4089 830

Italy

GRUNDFOS Pompe Italia S.r.l.
Via Gran Sasso 4
I-20060 Truccazzano (Milano)
Tel.: +39-02-95838112
Telefax: +39-02-95309290 / 95838461

Japan

GRUNDFOS Pumps K.K.
Gotanda Metalion Bldg., 5F,
5-21-15, Higashi-gotanda
Shiagawa-ku, Tokyo
141-0022 Japan
Phone: +81 35 448 1391
Telefax: +81 35 448 9619

Korea

GRUNDFOS Pumps Korea Ltd.
6th Floor, Aju Building 679-5
Yeoksam-dong, Kangnam-ku, 135-916
Seoul, Korea
Phone: +82-2-5317 600
Telefax: +82-2-5633 725

Latvia

SIA GRUNDFOS Pumps Latvia
Deglava biznesa centrs
Augusta Deglava ielā 60, LV-1035, Rīga,
Tālr.: + 371 714 9640, 7 149 641
Fakss: + 371 914 9646

Lithuania

GRUNDFOS Pumps UAB
Smolensko g. 6
LT-03201 Vilnius
Tel: + 370 52 395 430
Fax: + 370 52 395 431

Malaysia

GRUNDFOS Pumps Sdn. Bhd.
7 Jalan Peguam U1/25
Glenmarie Industrial Park
40150 Shah Alam
Selangor
Phone: +60-3-5569 2922
Telefax: +60-3-5569 2866

México

Bombas GRUNDFOS de México S.A. de C.V.
Boulevard TLC No. 15
Parque Industrial Stiva Aeropuerto
Apodaca, N.L. 66600
Phone: +52-81-8144 4000
Telefax: +52-81-8144 4010

Netherlands

GRUNDFOS Netherlands
Veluwezoom 35
1326 AE Almere
Postbus 22015
1302 CA ALMERE
Tel.: +31-88-478 6336
Telefax: +31-88-478 6332
e-mail: info_gnl@grundfos.com

New Zealand

GRUNDFOS Pumps NZ Ltd.
17 Beatrice Tinsley Crescent
North Harbour Industrial Estate
Albany, Auckland
Phone: +64-9-415 3240
Telefax: +64-9-415 3250

Norway

GRUNDFOS Pumper A/S
Strømsveien 344
Postboks 235, Leirdal
N-1011 Oslo
Tlf.: +47-22 90 47 00
Telefax: +47-22 32 21 50

Poland

GRUNDFOS Pompy Sp. z o.o.
ul. Klonowa 23
Baranowo k. Poznania
PL-62-081 Przeźmierowo
Tel: (+48-61) 650 13 00
Fax: (+48-61) 650 13 50

Portugal

Bombas GRUNDFOS Portugal, S.A.
Rua Calvet de Magalhães, 241
Apartado 1079
P-2770-153 Paço de Arcos
Tel.: +351-21-440 76 00
Telefax: +351-21-440 76 90

România

GRUNDFOS Pompe România SRL
Bd. Biruintei, nr 103
Pantelimon county Ilfov
Phone: +40 21 200 4100
Telefax: +40 21 200 4101
E-mail: romania@grundfos.ro

Russia

ООО Грундфос
Россия, 109544 Москва, ул. Школьная 39
Тел. (+7) 495 737 30 00, 564 88 00
Факс (+7) 495 737 75 36, 564 88 11
E-mail grundfos.moscow@grundfos.com

Serbia

GRUNDFOS Predstavništvo Beograd
Dr. Milutina Ivkovića 2a/29
YU-11000 Beograd
Phone: +381 11 26 47 877 / 11 26 47 496
Telefax: +381 11 26 48 340

Singapore

GRUNDFOS (Singapore) Pte. Ltd.
24 Tuas West Road
Jurong Town
Singapore 638381
Phone: +65-6865 1222
Telefax: +65-6861 8402

Slovenia

GRUNDFOS PUMPEN VERTRIEB Ges.m.b.H.,
Podružnica Ljubljana
Blatnica 1, SI-1236 Trzin
Phone: +386 1 563 5338
Telefax: +386 1 563 2098
E-mail: slovenia@grundfos.si

Spain

Bombas GRUNDFOS España S.A.
Camino de la Fuentecilla, s/n
E-28110 Algete (Madrid)
Tel.: +34-91-848 8800
Telefax: +34-91-628 0465

Sweden

GRUNDFOS AB
Box 333 (Lunnagårdsgatan 6)
431 24 Mölndal
Tel.: +46(0)771-32 23 00
Telefax: +46(0)31-331 94 60

Switzerland

GRUNDFOS Pumpen AG
Bruggacherstrasse 10
CH-8117 Fällanden/ZH
Tel.: +41-1-806 8111
Telefax: +41-1-806 8115

Taiwan

GRUNDFOS Pumps (Taiwan) Ltd.
7 Floor, 219 Min-Chuan Road
Taichung, Taiwan, R.O.C.
Phone: +886-4-2305 0868
Telefax: +886-4-2305 0878

Thailand

GRUNDFOS (Thailand) Ltd.
92 Chaloeam Phrakiat Rama 9 Road,
Dokmai, Pravej, Bangkok 10250
Phone: +66-2-725 8999
Telefax: +66-2-725 8998

Turkey

GRUNDFOS POMPA San. ve Tic. Ltd. Sti.
Gebze Organize Sanayi Bölgesi
İhsan dede Caddesi,
2. yol 200. Sokak No. 204
41490 Gebze/ Kocaeli
Phone: +90 - 262-679 7979
Telefax: +90 - 262-679 7905
E-mail: satis@grundfos.com

Ukraine

ТОВ ГРУНДФОС УКРАЇНА
01010 Київ, Вул. Московська 8б,
Тел.: (+38 044) 390 40 50
Факс.: (+38 044) 390 40 59
E-mail: ukraine@grundfos.com

United Arab Emirates

GRUNDFOS Gulf Distribution
P.O. Box 16768
Jebel Ali Free Zone
Dubai
Phone: +971-4- 8815 166
Telefax: +971-4-8815 136

United Kingdom

GRUNDFOS Pumps Ltd.
Grovebury Road
Leighton Buzzard/Beds. LU7 8TL
Phone: +44-1525-850000
Telefax: +44-1525-850011

U.S.A.

GRUNDFOS Pumps Corporation
17100 West 118th Terrace
Olathe, Kansas 66061
Phone: +1-913-227-3400
Telefax: +1-913-227-3500

Usbekistan

Представительство ГРУНДФОС в Ташкенте
700000 Ташкент ул.Усмана Носира 1-й
тупик 5
Телефон: (3712) 55-68-15
Факс: (3712) 53-36-35

Addresses revised 17.03.2008

GRUNDFOS A/S
DK-8850 Bjerringbro
Denmark
Telephone: +45 87 50 14 00

www.grundfos.com